Column & Fire Equipment Guidelines							Booth 18804 Room 251C
General booth https://www.na	n guidelines can amm.org/exhibit	be found here:	portant-guidelines	n or around your bo /display-guidelines-			
	/\	~~	~~	~~	/ \		17-2" / >
	×	×	×	×	×	×	→´3'-1" 2'-11"
				B'-8"			1'-10"
	×	×	×	×	×	×т	3'-1" ×
25'-5"	×	×	×	×	×	×	24'-10"
3'	×	×	×	×	×	×	×
							4'-2"
3'-	×	×	×	×	×	× Exit	3'-1"
251.01	×	×	×	×	×	×	×
REFERENCE GUIDELINES (unless otherwise noted on map) FS (Fire Strobe): ACC exhibit hall are 20' height; ACC lobbies are 6'7" height from the floor. Building Support Column FE (Fire Extinguisher): Must remain visible, accessible and unobstructed Building Support Column SP (Fire Speaker): 6"x6" & located at 9'9" height from the floor and shall be visible and unobstructed Exhibitors are free to brand & build around columns, as long as fire equipment is clear and nothing is adhered to the column or physical building.							
 PLEASE NOTE: This diagram indicates the size and approximate position of the obstruction within the booth with measurements. This may vary slightly onsite once the floor has been marked All fire equipment on columns must remain visible and accessible at all times and fire hoses must be clear to the aisle. Fire alarm devices have a strobe and a speaker at two different heights on a column Materials may not be affixed to columns; damage will be billed back to the exhibitor by the Anaheim Convention Center. 							